



HAND WINCHES

Due to our policy of continual development, dimensions, weight, and specifications may change without prior notice.

- Solid gear construction
- Black electrostatic finish to prevent rusting
- Zinc plating finish for resistance to corrosion and weather conditions
- Internally lubricated drum and pinion gear bushings
- Detachable moulded handle
- Formed reinforcements in frame for added strength
- Designed for deadload pulls – Maximum gradient 1:5
- Models 545B, 727B, 909B & 1136B are suitable for lifting
- Notes: Winches are not designed to secure boats to trailers – safety chains
- Never fully extend the steel wire rope
- Always keep at least 2 full turns of steel wire rope on the drum

HW0386, HW0545 & HW0727

Single Speed



HW0909 & HW01136

Dual Speed



**HW0545B, HW0727B,
HW0909B & HW1136B**

Product Code	Load Limit (Kg)	Speed	Gear Ratio	Steel Wire Rope Ø (mm)	Rope Capacity (m)	Drum Ø (mm)
HW0386	385kg	Single	3.2 : 1	5mm	10m	38
				6mm	7m	
HW0545	545kg	Single	04:01	5mm	18m	48
				6mm	15m	
HW0545B	545kg	Single	05:01	5mm	18m	49
				6mm	15m	
HW0727	727kg	Single	04:01	6mm	15m	48
HW0727B	727kg	Single	05:01	6mm	15m	49
HW0909	900kg	Dual	4 : 1/10 : 1	8mm	10m	48
HW0909B	900kg	Single	12:01	8mm	10m	48
HW1136	1100kg	Dual	5 : 1/12 : 1	8mm	16m	48
HW1136B	1100kg	Single	12:01	8mm	16m	60

